C.N.	Description .	Quantity	
S. No.	Description	Srinagar	Jammu
1.	IP Bullet Network Cameras 2MP – with specs;	As per	As per
	(Make: Hikvision / Samsung / Sony)	requirement	requirement
	2 Megapixel high-performance progressive scan CMOS May Image Receiving Full LID 1030 v 1080s		
	 Max Image Resolution Full HD 1920 x 1080p HD Real time video 		
	> Up to 30m IR with auto switch, Day/Night		
	> 0.07 lux @ F1.2, AGC ON, 0 lux with IR		
	> Shutter time 1/3s – 1/100,000s		
	➤ IP 66 weatherproof		
	Lens Mount M12		
	> 3D DNR & DWDR & BLC		
	Digital Wide Dynamic Range (WDR)		
	H.264/MJPEG Video compression		
	➤ Bit rate 32Kbps – 12 Mbps		
	Enabled Dual Stream		
	> IP66 rating		
	Power Consumption Max 5W (max 7W with ICR switch)		
	 Power Supply 12VDC ± 10% and PoE (802.3af) Vandal Proof Housing 		
	 Communication Interface RJ45 10/100M Ethernet Interface 		
	> Bracket included		
2.	IP Dome Network Cameras 2MP – with specs;	As per	As per
	(Make: Hikvision / Samsung / Sony)	requirement	requirement
	2 Megapixel high-performance progressive scan CMOS		
	Max Image Resolution Full HD 1920 x 1080p		
	HD Real time video		
	Up to 30m IR with auto switch, Day/Night		
	> 0.07 lux @ F1.2, AGC ON, 0 lux with IR		
	➤ Shutter time 1/3s – 1/100,000s		
	Lens Mount M123D DNR & DWDR & BLC		
	3D DNR & DWDR & BLCDigital Wide Dynamic Range (WDR)		
	 H.264/MJPEG Video compression 		
	➤ Bit rate 32Kbps – 12 Mbps		
	Enabled Dual Stream		
	Power Consumption Max 5W (max 7W with ICR switch)		
	Power Supply 12VDC ± 10% and PoE (802.3af)		
	Vandal Proof Housing		
	Communication Interface RJ45 10/100M Ethernet Interface		
3.	Network Video Recorder (NVR) 32 Channel with 2xSATA support	01	01
	5MP Camera – with specs;		
	(Make: Hikvision / Samsung / Sony) ➤ Support up to 32 Channel Video		
	> Support Third Party network Cameras		
	Two way audio input 1 Ch, RCA (2.0 Vp-p)		
	Incoming Bandwidth is 200Mbps		
	Up to 5 Megapixels resolution recording		
	Outgoing Bandwidth is 80 Mbps		
	Remote Connection is 128		
	Recording Resolution is 5MP / 3MP / 1080P / UXGA / 720P /		
	VGA / 4CIF / DCIF / 2CIF / CIF / QCIF		
	Frame rate: Main Stream 50fps (P) / 60 fps (N)		
	Frame rate: Sub Stream 50fps (P) / 60 fps (N)		
	HDMI / VGA Output: 1920 x 1080 / 60Hz, 1600 x 1200 / 60Hz, 1280 x 1024 / 60Hz, 1280 x 720 / 60Hz		
	> Decoding: 16 Ch @ 4CIF, 12 Ch @ 720P and 6 Ch @ 1080P		
	> 2 SATA interface for 2 HDDs		
	> Up to 4TB for each HDD		
	> 1 RJ45 10/100/1000 Mbps self adaptive Ethernet interface		
	2 20, 200, 2000 maps sen adaptive Effernet interface		

	> 1 x USB 2.0 and 1 x USB 3.0		
	HDD quota and group management		
	 12 VDC Power Supply Working Temperature -10 Degree to +55 Degree 		
		A	A - 11 - 11
4.	Surveillance Hard Disk Drive for Storage 2 TB, with Specs;	As per	As per
	(Make: Seagate / WD / Hitachi)	requirement	requirement
	Interface SATA 6Gb/s		
	Buffer Size 64MB		
	MTBF 100000 hour (s)		
	Advanced Format technology, AllFrame, IntelliPower,		
	IntelliSeek, Time Limited Error Recovery (TLER) and		
	Surveillance System Compatible		
	Internal Data Rate 110 Mbps		
	➤ Drive Transfer Rate is 600 Mbps	_	
5.	Networking PoE 8 ports Switch, with specs	As per	As per
	(Make: DLink / Tanda / Cisco)	requirement	requirement
	> 10/100/1000 Mbps Gigabit ports		
	Switching capacity 16 Gbps		
	Full Duplex Ethernet		
	Auto MDI/MDIX Crossover for all 8 ports	0.4	04
6.	Full HD LED Display 42 inches, with specs	01	01
	(Make: LG / Samsung / Sony)		
	Full HD 42inches		
	Resolution 1920 x 1080 Pixels		
	► HDMI Connectivity		
	> USB Interface		
7.	Online UPS 2KVA, with specs	01	01
	(Make: APC / Delta)		
	Two hours backup		
	> Rack Type		
8.	Networking Rack 9U	01	01
	(Make: DLink / Tanda / APC)		
9.	Cat 6 Cable	As per	As per
	(Make: DLink / Cisco / Leviton)	requirement	requirement
10.	Complete Installation, Testing and Commissioning charges including	As per	As per
	configuration of the Network, IP Cameras and NVR	requirement	requirement
	,	<u> </u>	